

Defacer Eraser[®] Graffiti Wipe Paint, Coating & Graffiti Removers Specification

Specifier Note: The information provided below is intended to guide the Architect in developing specifications for products manufactured by PROSOCO, Inc. and should not be viewed as a complete source of information about the product(s). The Architect should always refer to the Product Data Sheet and MSDS for additional recommendations and for safety information.

Specifier Note: Paragraph below is for PART 1 GENERAL, Quality Assurance.

Test Area

Test a minimum 4 ft. by 4 ft. area on each type of masonry. Use manufacturer's application instructions. Let the test panel dry 3 to 7 days before inspection. Use manufacturer's application instructions. Keep test panels available for comparison throughout the cleaning project.

Specifier Note: Paragraphs below are for PART 2 PRODUCTS, Manufacturers and Products.

Manufacturer: PROSOCO, Inc., 3741 Greenway Circle, Lawrence, KS 66046. Phone: (800) 255-4255; Fax: (785) 830-9797. E-mail: CustomerCare@proso.com

Product Description

Defacer Eraser[®] Graffiti Wipe is a solvent-based product that removes a variety of graffiti stains from most smooth masonry, split-faced concrete block, wood and metal surfaces. Graffiti Wipe is an easy-to-use graffiti remover that does not contain methanol, methylene chloride or other halogenated solvents prohibited on many projects.

Technical Data

FORM: Clear liquid with sweet almond odor

SPECIFIC GRAVITY: 1.04

pH: NA

WT/GAL: 8.69 lbs

ACTIVE CONTENT: NA

TOTAL SOLIDS: NA

FLASH POINT: >200 degrees F (>93 degrees C) (ASTM D 3278)

FREEZE POINT: NA

SHELF LIFE: 2 years

MAXIMUM VOC CONTENT: 30%

Limitations

- Product efficiency is reduced during cold weather.
- May damage synthetic or reflective glass.

Specifier Note: Paragraphs below are for PART 3 EXECUTION, Installation.

Application

Before applying, read "Protect" and "Precautionary Measures" sections in the Manufacturer's Product Data Sheet for Graffiti Wipe. Do not dilute or alter. Avoid generating aerosol mists during application.

Smooth or Protected Surface Application

1. Apply Graffiti Wipe liberally to a towel or piece of cloth. Scrub the surface with saturated cloth until the graffiti is removed.
2. Wipe the surface with a dry cloth to remove excess Graffiti Wipe and graffiti residue. If necessary, rinse the surface with hot or cold water to remove any remaining product residue.

Rough/Porous or Unprotected Surface Application

1. Apply Graffiti Wipe with a brush or low-pressure spray.
2. Allow to dwell for 3-5 minutes.
3. Pressure-water rinse. Hot water is preferable.