

## Enviro Klean® SafRestorer Cleaner Cleaning Specification

*Specifier Note: The information provided below is intended to guide the Architect in developing specifications for products manufactured by PROSOCO, Inc. and should not be viewed as a complete source of information about the product(s). The Architect should always refer to the Product Data Sheet and MSDS for additional recommendations and for safety information*

*Specifier Note: Paragraph below is for PART 1 GENERAL, Quality Assurance.*

### Test Area

Test a minimum 4 ft. by 4 ft. area on each type of masonry. Use manufacturer's application instructions. Let the test panel dry 3 to 7 days before inspection. Keep test panels available for comparison throughout the cleaning project.

*Specifier Note: Paragraphs below are for PART 2 PRODUCTS, Manufacturers and Products.*

**Manufacturer:** PROSOCO, Inc., 3741 Greenway Circle, Lawrence, KS 66046. Phone: (800) 255-4255; Fax: (785) 830-9797. E-mail: CustomerCare@prosoco.com

### Product Description

Enviro Klean® SafRestorer is a non-fuming restoration cleaner for removing stubborn atmospheric and carbon staining from masonry and stone for easy rinsing away. It restores the intended appearance of buildings soiled by decades of auto exhaust and other air pollutants. Enviro Klean® SafRestorer also gets rid of soiling and hard-to-remove deposits on window glass, including white scum.

Unlike many conventional restoration cleaners, low-odor, non-fuming SafRestorer is safe for use around most architectural metal. This highly efficient liquid restoration cleaner is suitable for a wide variety of stone and masonry, including unpolished limestone and marble.

### Technical Data

FORM: Clear, straw colored liquid with mild odor  
SPECIFIC GRAVITY: 1.11  
pH: 2.9  
WEIGHT/GALLON: 9.15 pounds  
FLASH POINT: not applicable  
FREEZE POINT: 28 degrees Fahrenheit (-2 degrees Celsius)  
SHELF LIFE: 2 years in tightly sealed, unopened container

### Limitations

- May not be suitable for some polished stone and glazed surfaces.
- Not intended for routine maintenance glass cleaning.
- Not for use on treated low-E glass; acrylic and polycarbonate sheet glazing; and glazing with surface-applied reflective, metallic or other synthetic coatings or films.

*Specifier Note: Paragraphs below are for PART 3 EXECUTION, Installation.*

### Application

Before applying, read "Preparation" and "Safety Information" sections in the Manufacturer's Product Data Sheet for SafRestorer. Use SafRestorer in concentrate or dilute with up to 3 parts water. Refer to Product Data Sheet for recommended dilution for intended use.

#### *Brick and Stone*

1. Working from the bottom to the top, thoroughly prewet the surface with fresh water.
2. Apply the cleaning solution freely from the bottom of the work area to the top.

3. Let the cleaning solution stay on the wall 5-15 minutes. If the cleaner starts to dry, reapply.
4. Reapply the cleaning solution to heavily soiled areas. Scrub gently.
5. Working from the bottom to the top, thoroughly rinse treated surfaces with clean water. Make sure to flush all spent cleaner and dissolved soiling from the surface, surface pores and adjacent non masonry surfaces.

*Glass*

Working from the bottom to the top, thoroughly prewet the glass with fresh water. Apply in concentrate directly to window. Let cleaner dwell for no more than five minutes. Thoroughly rinse spent cleaner and dissolved contaminants off glass with lots of fresh water.

SPECIFIER NOTE: Limit contact of cleaner with metal window frames, particularly architectural aluminum. If contact occurs, rinse immediately. In most cases, limited contact will not harm metal.

SPECIFIER NOTE: Repeated applications may damage glass and/or glazing. Always test for acceptable results before overall application.

**Cleanup**

Clean equipment with fresh water.