



PROSOCO®

Enviro Klean®

NEXT GENERATION CLEANERS

SafStrip 8

Enviro Klean® SafStrip® 8 is a neutral-pH stripping compound for nearly any hard surface – masonry, concrete, wood or metal. It bears the Enviro Klean® brand because it removes most high-strength paints and clear coats without the methylene chloride or methanol found in traditional solvent paint strippers.

Use SafStrip 8 to break the bond of the toughest oil-based “alkyd” paints, acrylics, lacquers and clear sealers. It also removes graffiti media such as spray paint and magic marker.

SafStrip 8’s gel-like consistency makes it hard to spill and easy to apply. It immediately emulsifies in water and may be rinsed off with cold water, hot water or steam.

ADVANTAGES

- Does not contain hazardous methylene chloride or methanol.
- Low odor. Low toxicity.
- Neutral pH.
- Slow drying.
- Needs no OverCoat paper.
- Effectively removes yellowed sealers and wax build-up as well as a variety of paint coatings.
- No surface neutralization required.
- Rinses with cold or hot water.
- Gel-like consistency permits safer application with less spillage.

Limitations

- Not for removal of cementitious coatings.
- Product efficiency is reduced when temperatures are below 40°F (4°C) and above 85°F (29°C).

REGULATORY COMPLIANCE

VOC Compliance

Enviro Klean® SafStrip® 8 is compliant with all national, state and district VOC regulations.

TYPICAL TECHNICAL DATA

FORM	Colorless gel
SPECIFIC GRAVITY	1.05
pH	8.02
WT/GAL	8.80 lbs
ACTIVE CONTENT	not applicable
TOTAL SOLIDS	not applicable
VOC CONTENT	30% maximum
FLASH POINT	>200° F (>93° C) ASTM D 3278
FREEZE POINT	not applicable
SHELF LIFE	2 years in tightly sealed, unopened container

SAFETY INFORMATION

Always read full label and SDS for precautionary instructions before use. Use appropriate safety equipment and job site controls during application and handling.

24-Hour Emergency Information:
INFOTRAC at 800-535-5053

Product Data Sheet

Enviro Klean® SafStrip® 8

PREPARATION

Protect people, vehicles, property, glass, solvent sensitive materials, roofing material, plants and all surfaces not set for stripping from product, splash, rinse, residue, fumes and wind drift.

Prepare surface by scraping or pressure rinsing to remove all peeling and/or loose coatings. Let the surface dry thoroughly before applying stripper.

Some metal finishes may be damaged by exposure to SafStrip 8. Always test. Protect with solvent-resistant polyethylene secured by duct tape. Sure Klean® Strippable Masking is not appropriate for use with stripping products.

Surface and Air Temperatures

Surface and air temperatures should be above 40°F (4°C) and below 85°F (29°C) during application.

Cleaning compounds are affected by temperature. Dwell times used successfully in one season may not be effective in another.

Equipment

Apply using a solvent-resistant brush or roller.

Rinse with enough water and pressure to flush spent cleaner and dissolved soiling from the surface and surface pores without damage. Inadequate rinsing leaves residues which may stain the cleaned surface.

Masonry-washing equipment generating 400–1000 psi with a water flow rate of 6–8 gallons per minute is the best water/pressure combination for rinsing porous surfaces. Use a 15–45° fan spray tip. Heated water (150–180°F; 65–82°C) may improve cleaning

efficiency. Use adjustable equipment for reducing water flow-rates and rinsing pressure as needed for sensitive surfaces.

Rinsing pressures greater than 1000 psi and fan spray tips smaller than 15° may permanently damage sensitive surfaces. Water flow-rates less than 6 gallons per minute may reduce cleaning productivity and contribute to uneven cleaning results.

Storage and Handling

Store in a cool, dry place. Always seal container after dispensing. Do not alter or mix with other chemicals. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperature of 45–100°F (7–38°C). Do not double stack pallets. Dispose of in accordance with local, state and federal regulations.

APPLICATION

Read “Preparation” and the Safety Data Sheet before use.

ALWAYS TEST a small area of each surface to confirm suitability, coverage rate and desired results before beginning overall application. Test with the same equipment, recommended surface preparation and application procedures planned for general application. Let surface dry thoroughly before inspection.

Dilution & Mixing

Do not dilute or alter. Apply as packaged.

BEST PRACTICES

Always test for suitability and results before overall application to find the proper dwell-time and the number of applications to remove all traces of coating. Test under weather conditions similar to those expected during cleaning. Let test areas dry thoroughly before inspection.

Cleaning compounds are affected by temperature. Dwell times used successfully in one season may not be effective in another.

Rinse with enough water and pressure to flush spent cleaner and dissolved soiling from the surface and surface pores without damage. Inadequate rinsing leaves residues which may stain the cleaned surface.

Masonry-washing equipment generating 400–1000 psi with a water flow rate of 6–8 gallons per minute is the best water/pressure combination for rinsing porous surfaces. Use a 15–45° fan spray tip. Heated water (150–180°F; 65–82°C) may improve cleaning efficiency. Use adjustable equipment for reducing water flow-rates and rinsing pressure as needed for sensitive surfaces.

Never go it alone. If you have problems or questions, contact your local PROSOCO distributor or field representative. Or call PROSOCO technical Customer Care, toll-free, at 800-255-4255.

Product Data Sheet

Enviro Klean® SafStrip® 8

Typical Coverage Rates

Always test to ensure desired results. Coverage estimates depend on surface texture and porosity.

- 25–50 square feet per gallon
- 2–5 square meters per gallon

Application Instructions

Do not let stripper dry on the surface. If tests indicate long dwell times, reapply to keep the previously applied material wet. Keep people away from the stripper.

Exterior Applications

1. Apply product 1/8-inch to 1/4-inch thick to dry surface.
2. Let the application dwell 15–60 minutes or until coating “lifts” or shows signs of dissolving. Periodic agitation with a stiff bristle brush improves penetration. Some coatings will need multiple applications/increased dwell time.
3. Remove stripper and residue with pressure-water rinse. Heated water may improve stripping efficiency.
4. Clean the stripped surface if needed with the appropriate PROSOCO product. Call Technical Customer Care toll-free at 800-255-4255 for cleaning recommendations.

Interior Applications

1. Follow steps 1 and 2 for Exterior Applications.
2. Using a low-pressure tank or pump-up sprayer, mist the treated surface with clean water. Water helps emulsify the old sealer and dilute the stripper so residues may be more easily removed.
3. Scrub surface until coatings are gone. Add more water to aid scrubbing. Ventilate to prevent accumulation of combustible vapors.
4. Use towels, mops or wet vacs to collect liquid residue. Locate wet vac motor outdoors well away from application site in a high area where vapors will not collect.
5. Thoroughly brush or mop-and-bucket rinse with clean water. If needed, clean surface with appropriate PROSOCO product.

Cleanup

Clean tools and equipment with high-flash aromatic naphtha or similar solvent. Cleaning with water may be sufficient if material has not dried.

WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care – technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our web site at www.prosoco.com, for the name of the PROSOCO representative in your area.