



# SAFETY DATA SHEET

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

<b>Product:</b>	<b>MEL-ROL® LM</b>	<b>Part Number:</b>	<b>6387000</b>
<b>Manufacturer:</b>	<b>W. R. Meadows®, Inc.</b>	<b>Address:</b>	300 Industrial Drive Hampshire, Illinois 60140
<b>Telephone:</b>	(847) 214-2100	In case of emergency, dial (800) 424-9300 (CHEMTREC)	
<b>Revision Date:</b>	9/9/2014		
<b>Product Use:</b>	Cold-Applied Water-Proofing Membrane		

## SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS

<b>HMIS</b>		<b>HAZARD STATEMENTS</b>		
Health	1	WARNING!		
Flammability	1	Causes skin irritation.		
Reactivity	0	<b>PRECAUTIONARY MEASURES</b>		
Personal Protection		Avoid direct contact.		

## SECTION 3: HAZARDS COMPONENTS

<b>Chemical Name:</b>	<b>CAS Number</b>	<b>% BY Weight</b>	<b>SARA 313</b>	<b>Vapor Pressure (mm Hg@20°C)</b>	<b>LEL (@25°C)</b>
1. Petroleum Asphalt	8052-42-4	50-55	No	N/A	N/A
2. Petroleum Oil Base Stock	64742-65-0	1-5	No	N/A	0.9

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313." *N/A = Not Applicable*

## SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

**EYE CONTACT:** Flush eyes with water for fifteen (15) minutes. If symptoms persist, seek medical attention.

**SKIN CONTACT:** Wash affected areas with mild soap and water.

**INHALATION:** Not expected to be an exposure route as supplied. If respiratory symptoms develop, seek medical attention.

**INGESTION:** Dilute with liquid unless the victim is unconscious or very drowsy. Do not induce vomiting. If vomiting spontaneously occurs, prevent lung aspiration. Seek immediate medical attention.

## SECTION 5: FIRE AND EXPLOSIVES HAZARDS

**FLASHPOINT:** Product will not flash due to water content.

**EXTINGUISHING MEDIA:** Water fog, foam, dry chemical.

**CHEMICAL/COMBUSTION HAZARDS:** Oxides and compounds of nitrogen/sulfur, carbon monoxide/dioxide, and incomplete combustion products.

**PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT:** Avoid smoke inhalation. Use appropriate personal protective equipment.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**SPILL OR LEAK PROCEDURES:** Avoid direct contact. Dike and contain spilled material. Remove source of spill if safe to do so. Apply absorbent and place clean-up material in sealed/marked containers for proper disposal. Clean-up materials will be classified as non-hazardous waste.

## SECTION 7: HANDLING AND STORAGE

**SAFE HANDLING PROCEDURES:** Avoid direct contact.

**SAFE STORAGE:** Prevent product from freezing.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Chemical Name:</b>	<b>OSHA</b>				<b>ACGIH</b>			
	<b>PEL</b>	<b>PEL/CEILING</b>	<b>PEL/STEL</b>	<b>SKIN</b>	<b>TLV</b>	<b>TLV/CEILING</b>	<b>TLV/STEL</b>	<b>SKIN</b>
1. Petroleum Asphalt	5 mg/m <sup>3</sup> *	N/E	N/E	No	0.5 mg/m <sup>3</sup> *	N/E	N/E	N/E
2. Petroleum Oil Base Stock	N/E	N/E	N/E	No	5 mg/m <sup>3</sup> +	N/E	N/E	N/E

\*: Asphalt Fumes      +: Mineral Oil Mist in Air      *N/E: Not Established*

**ENGINEERING CONTROLS:** None required under normal use conditions.

**PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses, chemical resistant gloves.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>BOILING POINT:</b> 212° F	<b>VAPOR DENSITY:</b> N/A	<b>% VOLATILE BY VOLUME:</b> N/A
<b>EVAPORATION RATE:</b> <1 (Ether=1)	<b>pH LEVEL:</b> N/A	<b>% VOLATILE BY WEIGHT:</b> 30
<b>WEIGHT PER GALLON:</b> 8.3	<b>PRODUCT APPEARANCE:</b> Black Liquid	<b>VOC CONTENT:</b> 0 g/L

## SECTION 10: STABILITY/REACTIVITY

**STABILITY:** Stable.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**CONDITIONS AND MATERIALS TO AVOID:** None recognized.

**HAZARDOUS DECOMPOSITION PRODUCTS:** None recognized.

# SAFETY DATA SHEET

Date of Preparation: 9/9/14

Page 2 of 2

6387000

## SECTION 11: TOXICOLOGICAL INFORMATION

**EYE CONTACT:** Direct contact may cause mild irritation.

**SKIN CONTACT:** Direct contact may cause slight skin irritation. Prolonged/repeated contact may result in irritation.

**INHALATION:** Not anticipated to be an exposure route.

**INGESTION:** Not anticipated to be an exposure route.

**SIGNS AND SYMPTOMS:** Symptoms of eye irritation include tearing, reddening, and swelling. Symptoms of skin irritation include redness and swelling. Gastrointestinal irritation symptoms include nausea, vomiting, and abdominal discomfort. Symptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and reduced lung function.

**AGGRAVATED MEDICAL CONDITIONS:** Pre-existing skin, eye, and respiratory disorders may be aggravated by exposure to this product.

**OTHER HEALTH EFFECTS:** ACGIH Classifies asphalt as *Not Classifiable as a Human Carcinogen; A4*.

## SECTION 12: ECOLOGICAL INFORMATION

**ECOTOXICITY:** N/E

**DEGRADABILITY:** N/E

**BIOACCUMULATIVE POTENTIAL:** N/E

**SOIL MOBILITY:** N/E

**OTHER ADVERSE EFFECTS:** None Recognized

## SECTION 13: WASTE DISPOSAL INFORMATION

**WASTE DISPOSAL INFORMATION:** Solidified product can be landfill disposed. No free liquids.

## SECTION 14: TRANSPORTATION INFORMATION

**HAZARDOUS/NON-HAZARDOUS MATERIAL:** Not regulated by DOT.

**UN NUMBER:** None.

**HAZARD CLASS:** N/A

**PACKING GROUP:** N/A

**UN PROPER SHIPPING NAME:** N/A

**ENVIRONMENTAL HAZARDS:** None recognized.

**BULK TRANSPORTATION INFORMATION:** None.

**SPECIAL PRECAUTIONS:** Prevent product from freezing.

## SECTION 15: REGULATORY INFORMATION

**OTHER REGULATORY CONSIDERATIONS:** None recognized.

## SECTION 16: OTHER INFORMATION

**PREPARATION DATE:** 9/9/2014

**PREPARED BY:** Dave Carey

---

---

*The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of this product described herein.*

---

---