

MATERIAL SAFETY DATA SHEET



Crete-Lease "Bond Breaker-Xtra"

HAZARD RATING:
4 = EXTREME
3 = HIGH
2 = MODERATE
1 = SLIGHT
0 = INSIGNIFICANT

	HEALTH	1
	FIRE	0
	REACTIVITY	0

IDENTIFICATION

PRODUCT NAME: Crete-Lease "Bond Breaker-Xtra" REVISION: 1-1-12
CHEMICAL FAMILY: Polymer Emulsion CAS #: Not applicable for this mixture
MANUFACTURER TELEPHONE NUMBER: (800) 367-2020 IN OHIO—(419) 669-2041
EMERGENCY PHONE NUMBER: (800) 424-9300 CHEMTREC (Transportation Emergencies)

COMPOSITIONAL INFORMATION

ALL Ingredients in this product are listed in the T.S.C.A. Inventory.

(No hazardous ingredients known at this time.)

Product is not a hazardous chemical as defined by OSHA Standard 29 CFR 1910.1200

Not a controlled product as defined by Part IV of the Controlled Products Regulations

Not a carcinogen as defined by NTP, IARC or OSHA.

ROUTE(S) OF EXPOSURE AND HEALTH EFFECTS

EFFECTS OF OVEREXPOSURE:

HEALTH HAZARDS: None known to occur.

CARCINOGENICITY: None known to exist.

SIGNS and SYMPTOMS OF EXPOSURE: None known to occur.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known to occur.

SPECIAL PRECAUTIONS

FIRST AID: Flush skin or eyes with water. If overexposure from inhalation is thought to occur, remove to fresh air. If ingested, call a physician.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep from freezing. Keep container closed when not in use.

OTHER PRECAUTIONS:

Common sense and good manufacturing practice should be used at all times.

This MSDS complies with OSHA's Hazard Communication Standard 29 CFR 1910.1200.

PHYSICAL DATA

FLASH POINT:	None	VAPOR DENSITY:	Lighter Than Air
LIQUID DENSITY:	Lighter Than Water	BOILING RANGE:	214°F
EVAPORATION RATE:	Slower than n-Butyl Acetate	VOC	2 g/L
WEIGHT PER GALLON:	8.2 Pounds		
APPEARANCE:	White Liquid		

