



SAFETY DATA SHEET


SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product:	PAC-IT® NON-METALLIC GROUT	Part Number: 8030000
Manufacturer:	W. R. Meadows®, Inc.	Address: 300 Industrial Drive Hampshire, Illinois 60140
Telephone:	(847) 214-2100	In case of emergency, dial (800) 424-9300 (CHEMTREC)
Revision Date:	9/9/2014	
Product Use:	Dry Pack Grout	

SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS

HMIS	HAZARD STATEMENTS
Health	2 DANGER!
Flammability	0 May cause cancer.
Reactivity	0 May cause skin irritation/burns.
Personal Protection	May cause burns to the eyes. May cause skin sensitization. May cause respiratory irritation. Causes lung damage through repeated/prolonged exposures.

PRECAUTIONARY STATEMENTS
 Avoid direct contact.
 Avoid dust inhalation.
 Use appropriate Personal Protective Equipment.



SECTION 3: HAZARDS COMPONENTS

Chemical Name:	CAS Number	% by Weight	SARA 313	Vapor Pressure (mm Hg@20°C)	LEL @25°C
1. Microcrystalline Silicon Dioxide	14808-60-7	55-60	No	N/A	N/A
2. Portland Cement	65997-15-1	35-40	No	N/A	N/A

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313." *N/A: Not Applicable*

SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Immediately flush eyes with water for fifteen (15) minutes. Seek immediate medical attention.

SKIN CONTACT: Remove contaminated shoes/clothing. Flush affected areas with water. If irritation develops/persists, seek medical attention.

INHALATION: Remove victim from exposure source. Treat symptomatically. If symptoms persist, seek medical attention.

INGESTION: Do not induce vomiting. If vomiting spontaneously occurs, keep the head below the hips to prevent lung aspiration. Seek immediate medical attention.

SECTION 5: FIRE AND EXPLOSIVES HAZARDS

FLASHPOINT: None.

EXTINGUISHING MEDIA: Not applicable--product will not burn.

CHEMICAL/COMBUSTION HAZARDS: None recognized. Material will not support combustion.

PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT: Avoid inhalation of dust if bags are broken. Use appropriate respiratory protection.

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Evacuate unauthorized personnel. Clean up using methods that will minimize dust creation or wet methods. Avoid inhalation of dust. Place in marked/non-leaking containers for disposal. Flush affected areas to remove trace residue.

SECTION 7: HANDLING AND STORAGE

SAFE HANDLING PROCEDURES: Avoid direct contact with this material as well as the creation of dust.

SAFE STORAGE: Store in cool, dry location away from moisture sources.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name:	OSHA				ACGIH			
	PEL	PEL/CEILING	PEL/STEL	SKIN	TWA	TLV/CEILING	TLV/STEL	SKIN
1. Microcrystalline Silicon Dioxide	*See Below	N/E	N/E	N/E	0.025 mg/m ³	N/E	N/E	N/E
2. Portland Cement	5 mg/m ³	N/E	N/E	N/E	1 mg/m ³	N/E	N/E	N/E

*: TWA Total Dust (30)/(%SiO₂ + 2) mg/m³. TWA Respiratory Fraction (10)/(%SiO₂ + 2) mg/m³ *N/E: Not Established*

ENGINEERING CONTROLS: Use equipment to keep dust levels below established exposure limits.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses, chemical-resistant gloves.

SAFETY DATA SHEET

Date of Preparation: 9/9/14	Page 2 of 2	8030000
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES		
BOILING POINT: Not Applicable	VAPOR DENSITY: Not Applicable	% VOLATILE BY VOLUME: Not Applicable
EVAPORATION RATE: Not Applicable	pH LEVEL: 10-12 (hydrated)	% VOLATILE BY WEIGHT: Not Applicable
WEIGHT PER GALLON: 20.62	PRODUCT APPEARANCE: Gray Solid	VOC CONTENT: 0 g/L
SECTION 10: STABILITY/REACTIVITY		
STABILITY: Stable.	HAZARDOUS POLYMERIZATION: Will not occur.	
CONDITIONS AND MATERIALS TO AVOID: When hydrated--acids, ammonium salts, aluminum metal.		
HAZARDOUS DECOMPOSITION PRODUCTS: None recognized.		
SECTION 11: TOXICOLOGICAL INFORMATION		
EYE CONTACT: Direct contact may result in severe irritation and possible chemical burns.		
SKIN CONTACT: May cause moderate skin irritation. Prolonged contact may result in chemical burns. Prolonged/repeated contact may cause sensitization reactions in susceptible individuals.		
INHALATION: Exposure may cause moderate irritation of the nose, throat, respiratory tract, and other mucous membranes. Inhalation of silica dust may result in lung disease (Silicosis).		
INGESTION: May cause mild to moderate irritation of the digestive tract. May cause stomach upset and vomiting.		
SIGNS AND SYMPTOMS: Symptoms of eye exposure include pain, burning, redness, and swelling. Symptoms of skin irritation include redness, burning, swelling, and rash. Symptoms of respiratory irritation include runny nose, shortness of breath, chest discomfort, and reduced lung function. Symptoms of gastrointestinal exposure include abdominal pain, nausea, and vomiting.		
AGGRAVATED MEDICAL CONDITIONS: Pre-existing skin, eye, and respiratory disorders may be aggravated by exposure to this product.		
OTHER HEALTH EFFECTS: Silicon Dioxide is listed by the IARC and NTP as being carcinogenic to humans (IARC Group 1A).		
SECTION 12: ECOLOGICAL INFORMATION		
ECOTOXICITY: N/E	DEGRADABILITY: N/E	BIOACCUMULATIVE POTENTIAL: N/E
SOIL MOBILITY: N/E	OTHER ADVERSE EFFECTS: N/E	
SECTION 13: WASTE DISPOSAL INFORMATION		
SECTION 14: TRANSPORTATION INFORMATION		
HAZARDOUS/NON-HAZARDOUS MATERIAL: Non-hazardous material.		
UN NUMBER: None.	HAZARD CLASS: None.	PACKING GROUP: None.
UN PROPER SHIPPING NAME: None.		
ENVIRONMENTAL HAZARDS: None.		
BULK TRANSPORTATION INFORMATION: Not applicable; product is not shipped in bulk configuration.		
SPECIAL PRECAUTIONS: None.		
SECTION 15: REGULATORY INFORMATION		
OTHER REGULATORY CONSIDERATIONS: None.		
SECTION 16: OTHER INFORMATION		
PREPARATION DATE:	9/9/2014	
PREPARED BY:	Dave Carey	

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of this product described herein.
